

§ 408.336

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kkg of seafood)	
TSS	26	14
Oil and grease	2.1	1.3
pH	(¹)	(¹)
	English units (lb/1,000 lb of seafood)	
TSS	26	14
Oil and grease	2.1	1.3
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

§ 408.336 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

Pollutant or pollutant property	Pretreatment standard
BOD ₅	No limitation.
TSS	Do.
pH	Do.
Oil and grease	Do.

[40 FR 55800, Dec. 1, 1975, as amended at 60 FR 33949, June 29, 1995]

§ 408.337 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Except as provided in §§ 125.30 through 125.32, the following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best conventional pollutant control technology:

40 CFR Ch. I (7–1–09 Edition)

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for thirty consecutive days shall not exceed—
	Metric units (kg/kkg of seafood)	
TSS	26	14
Oil and grease	21	1.3
pH	(¹)	(¹)
	English units (pounds per 1,000 lb of seafood)	
TSS	26	14
Oil and grease	2.1	1.3
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

[51 FR 24999, July 9, 1986]

PART 409—SUGAR PROCESSING POINT SOURCE CATEGORY

Subpart A—Beet Sugar Processing Subcategory

Sec.

409.10 Applicability; description of the beet sugar processing subcategory.

409.11 Specialized definitions.

409.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

409.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

409.14 Pretreatment standards for existing sources.

409.15 Standards of performance for new sources.

409.16 Pretreatment standards for new sources.

409.17 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Subpart B—Crystalline Cane Sugar Refining Subcategory

409.20 Applicability; description of the crystalline cane sugar refining subcategory.

409.21 Specialized definitions.

409.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best